

JOB:
REPRESENTATIVE:

 UNIT TAG:
 ENGINEER:
 CONTRACTOR:

 ORDER NUMBER:
 SUBMITTED BY:
 APPROVED BY:

 DATE:
 DATE:
 DATE:


CRS-HV

Coalescing medium style air & sediment separator with removable head for high velocity applications

DESCRIPTION

The Bell & Gossett CRS-HV is a combination air & sediment separator that utilizes a coalescing medium to remove impurities from high velocity HVAC systems. It features a stainless steel coalescing medium with 58% open area, removable end cover for coalescing medium access, and connections for an air vent, blow down valve, and skim valve. The product is designed, constructed, inspected and stamped per ASME Section VIII, Division 1.

CONSTRUCTION MATERIALS

Shell: Carbon Steel

Coalescing Medium: Stainless Steel

OPERATING DATA*

Max Working Pressure: 150 psig (1,034 kPa)


Max Temperature: 450°F (232°C)

Min Temperature: -20°F (-29°C)

* Consult factory for higher working pressures or temperatures.

SCHEDULE

PART NUMBER	MODEL NUMBER	INLET/OUTLET CONNECTION	RECOMMENDED CAPACITY IN GPM (M ³ /HR)	TAGGING INFORMATION	QUANTITY
5335-14F-15-001	CRS-14F-HV	14" Flanged	4,625 (1,050)		
5335-16F-15-001	CRS-16F-HV	16" Flanged	5,785 (1,315)		
5335-18F-15-001	CRS-18F-HV	18" Flanged	7,460 (1,695)		
5335-20F-15-001	CRS-20F-HV	20" Flanged	8,950 (2,035)		
5335-22F-15-001	CRS-22F-HV	22" Flanged	10,855 (2,465)		
5335-24F-15-001	CRS-24F-HV	24" Flanged	13,050 (2,965)		




DIMENSIONS AND WEIGHTS

MODEL NUMBER	DIMENSIONS - INCHES (mm)										SHIPPING WEIGHT LBS (KG)	FLOODED WEIGHT LBS (KG)	CV
	A	B	C	D	E	F	G	H	J	K			
CRS-14F-HV	114.00 (2896)	54.00 (1372)	45.00 (1143)	33.00 (838)	28.00 (711)	12.50 (318)	3/4" NPT	1/2" NPT	2" NPT	6.50 (165)	1764 (801)	4171 (1892)	2,362
CRS-16F-HV	114.00 (2896)	54.00 (1372)	50.00 (1270)	37.00 (940)	32.00 (813)	12.50 (318)	3/4" NPT	1/2" NPT	2" NPT	6.50 (165)	2093 (950)	5259 (2386)	3,255
CRS-18F-HV	115.00 (2921)	54.00 (1372)	56.00 (1422)	42.00 (1067)	36.00 (914)	12.50 (318)	3/4" NPT	1/2" NPT	2" NPT	8.50 (216)	2487 (1129)	6585 (2987)	4,048
CRS-20F-HV	120.00 (3048)	54.00 (1372)	61.50 (1562)	46.00 (1168)	40.00 (1016)	14.00 (356)	3/4" NPT	1/2" NPT	2" NPT	8.50 (216)	3075 (1395)	8154 (3699)	5,049
CRS-22F-HV	110.00 (2794)	54.00 (1372)	62.00 (1575)	53.00 (1346)	48.00 (1219)	15.50 (394)	3/4" NPT	1/2" NPT	2" NPT	5.50 (140)	3531 (1602)	10107 (4585)	6,216
CRS-24F-HV	110.00 (2794)	54.00 (1372)	62.00 (1575)	53.00 (1346)	48.00 (1219)	15.50 (394)	3/4" NPT	1/2" NPT	2" NPT	5.50 (140)	3593 (1630)	10269 (4658)	8,234

IMPORTANT NOTES

1. Consult IOM 0121-01 for safety and service instructions.
2. Lifting lugs are for transportation and installation of the empty vessel, and are not to be used for complete or partial support of the flooded vessel.
3. Welding to the pressure vessel boundary will void the ASME stamp.
4. Dimensions subject to change. Not to be used for construction purposes.



Xylem |'zīləm|

- 1) The tissue in plants that brings water upward from the roots;
- 2) a leading global water technology company.

We're a global team unified in a common purpose: creating advanced technology solutions to the world's water challenges. Developing new technologies that will improve the way water is used, conserved, and re-used in the future is central to our work. Our products and services move, treat, analyze, monitor and return water to the environment, in public utility, industrial, residential and commercial building services settings. Xylem also provides a leading portfolio of smart metering, network technologies and advanced analytics solutions for water, electric and gas utilities. In more than 150 countries, we have strong, long-standing relationships with customers who know us for our powerful combination of leading product brands and applications expertise with a strong focus on developing comprehensive, sustainable solutions.

For more information on how Xylem can help you, go to www.xylem.com



Xylem Inc.
8200 N. Austin Avenue
Morton Grove, IL 60053
Tel: (847) 966-3700 Fax: (847) 965-8379
www.xylem.com/bellgossett

Xylem and Bell & Gossett are registered trademarks of Xylem Inc. or one of its subsidiaries. All other trademarks or registered trademarks are property of their respective owners.
© 2024 Xylem A-326-14D July 2024